



RT4MC-B

4 pole TINY xlr male cable connector, black metal shell, gold plated contacts, bulk packaging available (*-D)

- Easy to assemble
- Robust metal housing with best flex relief
- Shielded system – high noise immunity and EMI protection
- Intuitive and rugged locking mechanism provides secure locking system
- Millionfond proven chuck type strain relief – up to 4.00 mm cable diameter
- Keyed insert and strain relief to avoid mispositioning / rotation of insert respectively cable



Technical Information [hide](#)

Product

Title RT4MC-B

Gender male

Electrical

Contact resistance < 10 mΩ

Dielectric strength > 0.5 kVdc

Insulation resistance > 1 GΩ

Rated current per contact < 5 A

Mechanical

Cable O.D. 2.0 - 4.0 mm

Lifetime > 5000 mating cycles

Wiresize 0.22 mm²

Wiresize 24 AWG

Wiring Solder contacts

Material

Bushing ABS / TPU

Contact plating Au

Contacts Bronze (CuSn6)

Insert PA 6.6 30 % GF

Shell Zinc diecast (ZnAl4Cu1)

Shell plating Black

Strain relief POM

[Home](#) [Products](#) [Contact](#) [Downloads](#)

Solderability	Complies with IEC 68-2-20
---------------	---------------------------

Temperature range	-30 °C to +85 °C
-------------------	------------------

Accessories

BRT-L



Data subject to change without prior notice. © 2012 NEUTRIK AG ® ALL RIGHTS RESERVED

REAN
REAN a brand of Neutrik AG